



Warning horn in stable plastic housing (ABS)

Features

- Simple maintenance
- Continuous operation
- Long life-time
- Reliable

Technical Data
Electrical

Power Supply	110 - 240 V AC, 50 Hz or 9 - 28 Vdc
Power Consumption	Max. 68 mA
Audio frequency	32 arbitrary sounds, incl. DIN tone
Acoustic pressure	64 dB (A) - 111 dB (A)

Operating Environment

Humidity	0 – 95 % r.H non-condensing
Working temperature	-10 °C to +55 °C
Storage temperature	-10 °C to +55 °C
Pressure range	Atmospheric ± 10 %

Physical characteristics

Enclosure material	Thermoplastic (ABS), shock-resistant
Enclosure colour	Red
Dimensions (D x H)	Appr. 93 x 93 mm
Weight	0.32 kg
Protection class	IP 54
Mounting	Wall and ceiling installation
Cable entry	Appr. 12 mm diameter
Wire connection	Screw-type terminals, min. 0.28 mm ² , max. 2.5 mm ²

Directives	VdS
-------------------	-----

Application

All-purpose audio warning hooter with 32 adjustable sounds, incl. DIN tone for fire-detection and safety systems in accordance with the VdS directives.

Ordering Codes

AAW 230	Warning Horn 230Vac, 98 dB
AAW 24	Warning Horn 24Vdc, 98 dB

We cannot be held responsible for errors in the manual/datasheet and reserve the right to correct any errors and to make product improvements, which may affect the accuracy of the manual/datasheet, without prior notice.