



Combined warning horn and flashlight in stable plastic housing (ABS)

Features

- Simple maintenance
- Continuous operation
- Long life-time
- Reliable

Technical Data

Electrical

Power Supply	18 – 30 Vdc
Power Consumption	Max. 68 mA
Audio frequency	32 arbitrary sounds, incl. DIN tone
Acoustic pressure	Max. 100 dB(A)

Operating Environment

Humidity	0 – 95 % r.H non-condensing
Working temperature	-10 °C to +55 °C
Storage temperature	-10 °C to +55 °C
Pressure range	Atmospheric ± 10 %

Physical characteristics

Enclosure material	Thermoplastic (ABS), shock-resistant
Enclosure colour	Red
Dimensions (D x H)	Appr. 93 x 93 mm
Weight	0.32 kg
Protection class	IP 54
Mounting	Wall and ceiling installation
Cable entry	Appr. 12 mm diameter
Wire connection	Screw-type terminals, min. 0.28 mm ² , max. 2.5 mm ²

Directives	VdS
-------------------	-----

Application

All-purpose audio warning hooter with integrated xenon flashlight for acoustic and optical warning with separate actuation

Ordering Code

OAW 24	Warning Horn/Flashlight 24Vdc
---------------	-------------------------------