



# Offshore Fail Safe Actuator IP66

## Closing time < 1 second

Nov.16

### Features

- High efficiency
- Integrated heating system guarantees operation down to - 40C degrees with rated torques
- Non-loaded spring return with guaranteed service life of 5000 cycles
- External function test using switch
- Three adjustable running times, adjustable externally without tools using switch
- External display of operating states using coloured LEDs
- IP66 protection class, sealed against dust and protected against strong water jets



**F500, F5R0,**

**5 Nm up to damper area approx 1,0m<sup>2</sup>, 10, 20 or 30 seconds running time, closing time under 1 second**

**F500 54P**     24Vac/dc     on/off, öka/minska     .....

**F5R0 53P**     230Vac     on/off, öka/minska     .....

**10 Nm up to damper area approx 2,0m<sup>2</sup>, 10, 20 or 30 seconds running time, closing time under 1 second**

**F500 104P**     24Vac/dc     on/off, öka/minska     .....

**F5R0 103P**     230Vac     on/off, öka/minska     .....

**15 Nm up to damper area approx 3,0m<sup>2</sup>, 10, 20 or 30 seconds running time, closing time under 1 second**

**F500 154P**     24Vac/dc     on/off, öka/minska     .....

**F5R0 153P**     230Vac     on/off, öka/minska     .....